

NOTE

Inside Height as Specified

Inside Roof, Floor and Side Wall Openings as Specified

Maximum inside Height for 2 Piece Manhole 10'-0" Maximum inside Height of Each Additional Piece 5'-0"



MH8X12

FILE NAME: 324UCPMH8X12_ISO.DWG

issue date: January, 2008 www.oldcastleprecast.com

8'-0" x 12'-0" x Variable I.D. Utility Vault


Copyright © 2008 Oldcastle Precast


12'-0" A 8'-0"

NOTES:

- 1. Concrete : 5,000 P.S.I Minimum Strength @ 28 Days
- 2. Steel Reinforcing— ASTM A-615, Grade 60.
- 3. Cover to Steel-1" Minimum
- 4. Vault are Designed to Meet ASTM C858 and ACI 318 with AASHTO HS-20 Loading
- 5. Earth Cover -0 to 5 Feet Max. Minimum
- 6. Construction Joint-Sealed with 1"Dia Butyl Rubber or Equivalent
- 7. Wall Thickness Available in 6", 8" & 10"

PLAN VIEW





SECTION A-A

END VIEW



MH8X12

FILE NAME: 324UCPMH8X12_DET.DWG

issue date: January, 2008 www.oldcastleprecast.com

8'-0" x 12'-0" x Variable I.D. Utility Vault

Copyright © 2008 Oldcastle Precast