

MODEL & MATERIAL

4 Way of 6 1/4"

High Density Polyethylene

4 WAY XL UNIT

14 3/4" x 14 3/4" x 44"

Lay length: 42 1/4"

36.4 lbs

Pallet Qty: 12



OPTIONS



End Caps:

- Bell End Cap
- Spigot End Cap



Adapters:

- Single Duct Adapter
- Double Socket
- Double Spigot


Other Accessories:

- Spring Clips
- Neoprene Gasket
- Flexible Duct

RAW MATERIAL SPECIFICATION

Material Properties

Material Profile	High Density Polyethylene (HDPE)	Black
Tensile Strength	ISO 527	22-26 MPA
Flexural Modulus	ISO 178	800 to 1100 N/mm ²
Notched Izod Impact Strength	ISO 180 - 1A	4 - 6KJ/m ³
Density	ISO 1183-1	0.955 - 0.958 g/cm ³
Service Temperature	-	-40 to +80 °C
Surface Resistivity	ASTM D257-14	> 5.24E+15 ohm/square
Volume Resistivity	ASTM D257-14	> 2.276.39E+15 ohm/cm
Fire Performance	UL94	HB
Water Absorption (Non polar polymer)	-	0.01%

 **WARNING:** Cancer - www.P65Warnings.ca.gov

All information contained on this sheet is current at the time of publication.
Oldcastle reserves the right to discontinue or update product information without notice.

Revision 03/20/19
© 2019 Oldcastle Infrastructure, Inc.